

DST400 Series Order Guide Effective January 1, to June 30, 2018

WAHL DST400 METER & PROBE ORDER GUIDE

Code	Step 1 - order Digi-Stem DST400 Thermocouple Meter (NIST purchased separately)	Price	Add \$	
DST400K	Digi-Stem T/C Meter, LCD, Factory configured for Type K T/C, ("C" Battery included), -40° to 2500°F (-40° to 1371°C)		\$	
DST400J	Digi-Stem T/C Meter, LCD, Factory configured for Type J T/C, ("C" Battery included), -40° to 2192°F (-40° to 1200°C)		\$	
DST400T	Digi-Stem T/C Meter, LCD, Factory configured for Type T T/C, ("C" Battery included), -40° to 752°F (-40° to 400°C)		\$	
DST400E	Digi-Stem T/C Meter, LCD, Factory configured for Type E T/C, ("C" Battery included), -40° to 1832°F (-40° to 1000°C)		\$	
DST400S	Digi-Stem T/C Meter, LCD, Factory configured for Type S T/C, ("C" Battery included), 32° to 3200°F (0° to 1760°C)		\$	
I ¹ Models	Digi-Stem T/C Meter, LCD, International ("AA" Battery included) (add "I" to end of Model number)	N/C	____*	
NB ¹ Models	Digi-Stem T/C Meter, (No Battery incl). Requires purchase of C battery from local supplier (add "NB" to end of Model number. Subtract charge) IF NB (NO BATTERY) SUBTRACT -		\$	
P Models	Panel Mount (add "P" to end of Model number) IF P (PANEL MOUNT) ADD +		\$	
Stop here if ordering meter only. If ordering a probe, please continue with Step 2.	Code	Step 2 - order Probe Connection (Select One)	Select or Add \$	
	DST4	DST400 Series Grounded Probe	\$	
	DSX4	DSX400 Series Ungrounded Probe	\$	
	Code	Thermocouple Type (Select One)	Select or Add \$	
	K	Type K Thermocouple	N/C	____*
	J	Type J Thermocouple	N/C	____*
	T	Type T Thermocouple	N/C	____*
	E	Type E Thermocouple	Call	
	S	Type S Thermocouple	Call	
	Code	Process Connection (Select One)	Select or Add \$	
01	1/2" NPT Fitting	\$		
02	3/4" NPT Fitting, Welded only	\$		
03	1-1/2" Dia, 3-A Sanitary Std 74-06; Stem Type Code "2" (Stem Material Codes 3 or 4 only)	\$		
04	2" Dia, 3-A Sanitary Std 74-06; Stem Type Code "2" (Stem Material Codes 3 or 4 only)	\$		
05	2-1/2" Dia, 3-A Sanitary Std 74-06; Stem Type Code "2" (Stem Material Codes 3 or 4 only)	\$		
06	3" Dia, 3-A Sanitary Std 74-06; Stem Type Code "2" (Stem Material Codes 3 or 4 only)	\$		
09	Unthreaded Transition Fitting	\$		
Code	Mounting Style (Select One) For Back, Left or Right Side Mount specify Code B-Rigid, & add #13146	Select or Add \$		
A	Adjustable Angle (Not available on Remote Stems)	\$		
B	Rigid (Bottom Connected)	NC	____*	
C	Remote (Mounting Bracket not included)	\$		
Code	Stem Type (Select One)	Select or Add \$		
2	Welded	N/C	____*	
3	Spring Loaded. Process Connection Codes "01, 02" only. Stem Material Codes "1, 3, 5, 7" only	\$		
¹ DST Meters come standard with a "C" cell battery, ready for ground shipment in the contiguous 48 states and some areas of Canada. For air shipments, either an "I" model with a "AA" battery, or "NB" model with no battery, is required to avoid additional charges in compliance with transportation regulations regarding "C" cell lithium metal batteries. Specify on order form.	Code	Stem Material/Construction/Length (1-72 Inches) (Select One)	Price	Add \$
	1	304 SS, 1/4" Dia, Temp Rating 500°F (260°C), Specify exact length: _____	@ /inch	\$ _____
	2	304 SS, 3/8" Dia, Temp Rating 500°F (260°C), Specify exact length: _____	@ /inch	\$ _____
	3	316 SS, 1/4" Dia, Temp Rating 500°F (260°C), Specify exact length: _____	@ /inch	\$ _____
	4	316 SS, 3/8" Dia, Temp Rating 500°F (260°C), Specify exact length: _____	@ /inch	\$ _____
	5	304 SS, 1/4" Dia, Temp Rating 1500°F (815°C), Specify exact length: _____	@ /inch	\$ _____
	6	304 SS, 3/8" Dia, Temp Rating 1500°F (815°C), Specify exact length: _____	@ /inch	\$ _____
	7	316 SS, 1/4" Dia, Temp Rating 1500°F (815°C), Specify exact length: _____	@ /inch	\$ _____
8	316 SS, 3/8" Dia, Temp Rating 1500°F (815°C), Specify exact length: _____	@ /inch	\$ _____	
Insert Model Number Code in white boxes below to construct Part Number for product desired, and carry over to next page.	Code	Stem Lengths (Specify) (Specify exact length desired)		
	01X - 72X	1 to 72 Length in inches - 13X = 13 inch, 14X = 14 inch, 15X = 15 inch, etc. For fractional lengths substitute X with: A = 1/4", B = 1/2", C = 3/4", Example: 13B = 13-1/2". Specify Code from Length above.	Pricing for Stem Length above	
Stop here if ordering Adjustable Angle or Rigid Probe.			If ordering Remote Probe continue with options on next page.	
DST400__			Subtotal	\$

DST400 Series Order Guide Effective January 1, to June 30, 2018

WAHL DST400 METER & PROBE ORDER GUIDE					
Continue below if ordering Remote Probe.					
Code	Step 3 - order Remote Probe Cable Type/Length (Select One)			Price	Add \$
1	PVC, Temperature Rated 105°,	Specify exact length desired: _____		@ /meter	\$ _____
2	Teflon, Temperature Rated 204°C,	Specify exact length desired: _____		@ /meter	\$ _____
3	Armored Stainless Steel - .195" Diameter, over Teflon wire,	Specify exact length desired: _____		@ /meter	\$ _____
Code	Remote Cable Length (Specify)				
02-99	2 to 99 Length in meters - 02 = 2 meters, 03 = 3 meters, 24 = 24 meters, etc. Specify Code from Length above.			Pricing is above	
Remote Probe Ordering information				Subtotal	\$
Remember to include T/C probe number from previous page and combine with remote probe number from this page to obtain final part number.				Subtotal from previous page	\$
				TOTAL	\$

Meter	Probe	Adjustable Angle and Rigid Probe Ordering Information (from previous page)					Remote Probe Ordering Information (from above)	
DST400__	DS_4							

Wahl DST400 Series Optional Accessories Order Guide				
Step 4 - order DST400 Series Software and Accessories			Price	Add
DSTCAL	DST400 Series Calibration Software Kit (includes USB Cable, DST/USB Interface Module, and Digi-Stem Serial Interface Cable)			\$
DST400 Series Meter Accessories and NIST Traceable Certificate of Conformance				
DSA3030	Wall Mount Bracket (for Remote Mount units)			\$
DSA3031	Wall Mount Bracket (for Remote Mount units) with Grounding Lug			\$
DSA3062	Spare Lithium Thionyl Chloride "C" Battery, 3.6V, for all DST meters except FM version			\$
12234-03	Spare Lithium Thionyl Chloride "AA" Battery for I versions			\$
	Calibration & Firmware Upgrades ²		See Calibration Price List	\$
	NIST Traceable Certificate of Conformance of System & Firmware Upgrades ²		See Calibration Price List	\$
	NIST Traceable Certificate of Conformance of System & Firmware Upgrades ²		See Calibration Price List	\$
	Add \$ per User Specified Test Point.		See Calibration Price List	\$
13146X	90 Degree Elbow ³ for Rigid Stem models, Specify X: Back Connection (B), Left (L) or Right Side (R) Mount			\$

² Upgrades If applicable, are included in price.
³ For Back, Left, or Right Side Mounting Style specify Code B-Rigid Stem, and add #13146X - 90° Elbow accessory, and specify X as shown above.