

WAHL FEVER ALERT THERMOMETER

Screen for possible fever with the **NEW!** Wahl DHS110S Infrared Thermometer!

An early warning device to screen people quickly and easily for possible fever, the **Wahl DHS110S Pocket Fever Alert Infrared Thermometer** can potentially limit the infectious transmission of disease during an outbreak. The Pocket Fever Alert can be part of a plan to protect the population from a possible pandemic.

Non-intrusive, and non-contact; in less than a second it can detect elevated body temperatures, indicating possible fever. Simply press, scan, and view reading on the large LCD screen. **AUDIBLE and VISUAL ALARMS** alert the user if a pre-defined threshold is exceeded.

Affordable and easy to use, the Pocket Fever Alert is a great choice to use when screening the public to potentially minimize the spread of flu in both the workplace and public venue's.

SPECIFICATIONS	
Model Number	DHS110S Pocket Fever Alert
Temperature Range	32° to 122°F (0° to 50°C)
Accuracy	±0.5°F (86°F to 108°F) ±0.3°C (30°C to 42°C)
Repeatability	< 0.2°C
Distance to Target Ratio	15:1
Spectrum	7 µm to 18 µm
Resolution	0.1°C or 0.1°F
Backlight	Yes
Display Hold	Yes
MAX	Yes
Alarm Setup	Yes, Audio and Visual
Alarm Response	< 200 ms
High Alarm	Yes, user defined (0.1°C/°F) increments
Environment	0°C ~ 45°F
Measuring Distance	11.81 to 19.68 inches (30 cm ~ 50 cm)
Battery	9V
Weight	< 7.05oz (200g)
Dimensions	6.14 x 2.12 x 1.18 inches (156mm x 54mm x 30mm)
Included Accessories	9V Battery, Carrying Case and Wrist Strap
Optional Accessories	Portable Calibration Black Body

*Specifications subject to change without notice.
Always verify human temperature with a medical thermometer.*



**Backed by Palmer Wahl's
Service and Warranty!**



Wahl Pocket
Infrared
Thermometer
DHS110S
with wrist strap

DHS110S Features

- **AUDIBLE and VISUAL Alarms** alert when pre-defined threshold is exceeded
- **Non-contact skin temperature measurement**
- **Quick & easy screening**
- **Large, Easy-To-Read LCD Digits with Switch on Back Light for Low Light Conditions**
- **Low-Drain Battery Operation with Low Battery Indicator**
- **Display Hold of Last Reading for 6 Seconds**
- **Optional Black Body (shown right) verifies accuracy of the imager**



Calibration Services Available

PALMER Wahl
INSTRUMENTATION GROUP
Continuous Innovation Since 1836
ISO9001:2000 CERTIFIED

(800) 421-2853 • FAX (828) 658-0728 • www.palmerwahl.com

08/09 Rev B